



## **Data Collection Terminal**

It is a compact data collection solution designed for Laundry monitoring. With Sbox, you can monitor data, define alarms, analyze data and receive notifications via SMS / E-Mail. With the data backup specification, you can save all historical data. It is a plug & play solution that does not require any computer or software for installation. Compatible with all kinds of systems with wide communication protocols.



## **General Specifications**

- Web based interface
- Customizable dashboard
- Alarm-Notification management
- Rule management
- Monitoring from the center
- Consumption monitoring
- Real-time tracking (Trend and Table)
- Reporting
- Downtime tracking
- **Production counter**
- **PLC Communication support**

- Modbus TCP/RTU communication support
- OPC UA client support
- 4-20mA sensor support
- PT100 sensor support
- Dry contact sensor input (4pcs)
- Alarm siren output
- Relay output (2 pcs )
- Built in Wi-Fi
- 3G modem support
- IP/USB camera support
- Onboard temperature and humidity sensors



## **Technical Specifications**

| Internal Temperature and Humidity Sensor    | 1   |
|---|---|
| Internal Temperature Sensor Measuring Range | 0 - 60 °C   |
| Internal Temperature Sensor Sensitivity     | Precision < 0.5%  |
| Internal Humidity Sensor Measuring Range    | Relative Humidity 0 - 100                                 |
| Humidity Sensor Sensitivity                 | Sensitivity < 3%  |
| Digital Sensor Port (1-Wire)                | 1 (Max. 16 pcs 1-Wire Sensor)                             |
| Max. 1-Wire Sensor Distance                 | 50 m  |
| Memory                                      | 8 GB  |
| Processor                                   | 4-Core ARM  |
| Digital Input                               | 4 (5 - 24 VDC)  |
| Digital Output                              | 2 (Max. 30 VDC)   |
| USB 2.0 Port                                | 3   |
| HDMI Output                                 | 1   |
| 10/100 Mb Ethernet                          | 1   |
| Serial Communication (RS-485)               | 1   |
| External HDD, Keyboard, Mouse Connection    | USB   |
| Supply Voltage                              | 24 VDC  |
| Power Consumption                           | 10 W  |
| Operating Temperature Range                 | 0 - 60 ° C  |
| Operating Humidity Range                    | 10% - 90% (Non-condensing)                                |
| Physical Dimensions                         | 60x90x85 mm   |
| Mounting Type                               | DIN Rail  |
| EMC Compatibility                           | EN 61000-6-4 / EN 61000-6-2                               |
| Product Warranty                            | 1 Year  |
| Network Protocols                           | HTTP, HTTPS, SNMP Traps, TCP Socket IO, MQTT, Modbus TCP, |

HTTP, HTTPS, SNMP Traps, TCP Socket IO, MQTT, Modbus TCP, Modbus RTU, OPC UA